

## S22 clip-in swing down system



S22 clip-in is a durable, swing down metal tile available perforated or plain. The plain surface is suitable for hygienic environments; catering or healthcare. The perforated surface helps to create a calm and quiet environment, thus aiding work and recovery.

If you would like further information, please contact us via telephone or email:  
T: +44(0)1753 552 489  
E: [enquiries@owa-ceilings.co.uk](mailto:enquiries@owa-ceilings.co.uk)

[www.owa-ceilings.co.uk](http://www.owa-ceilings.co.uk)

**OWA**

# S22 clip-in swing down system

---

## Features:

- Premium quality, German engineered
- Concealed suspension system
- Clip-in swing down enables access to services above
- Plain L0 is suitable for hygienic and positive/negative pressure rooms (sealing required)
- Perforated tiles provide excellent sound absorption

<b>Collection</b>	OWAtecta
<b>Material</b>	Galvanised sheet steel, approx. 0.6 mm
<b>Modules</b>	600 x 600 mm (stocked)
<b>Surface*</b>	Plain L0 and perforated Rd1522 (black acoustic fleece)
<b>Colour*</b>	RAL 9010 pure white and RAL 9010 anti-bac (Plain L0)
<b>Edges</b>	Bevelled (edge 01)



<b>Sound absorption</b>	Rd1522 with acoustic pad: $\alpha_w = 0.90$ (class A) Rd1522 with fleece: $\alpha_w = 0.70$ (class C)
<b>Sound insulation</b>	Rd1522 with pad and mineral tile: $D_{nfw} = \text{up to } 45 \text{ dB}$ Rd1522 with fleece: $D_{nfw} = 16 \text{ dB}$
<b>Reaction to fire</b>	A2-s1,d0 (BS EN 13501-1)
<b>Fire resistance</b>	N/A
<b>Cleanrooms</b>	Yes (Plain L0 - ISO 14644-1 class 1)
<b>Hygiene</b>	Yes (Plain L0)
<b>System Weight</b>	Approx. 6.8 kg/m <sup>2</sup>
<b>Cleaning</b>	Vacuum, wipe or dust only
<b>Sustainability</b>	100% recyclable
<b>Warranty</b>	Tile = 10 years, installed system = 30 years**



\* Other colours and surfaces also available.

\*\* The limited warranty is project specific. To comply, an accompanying warranty document must be completed and signed by the installing contractor and OWA project manager. If not, the standard 10 year product warranty will apply.