

S45 T15 lay-in system



S45 lay-in is a premium, durable metal tile with a perforated surface. Designed to be installed with our standard 15 mm grid and supplied with a tegular edge (8 mm drop). Ideal for retail, offices, education, industrial, catering or healthcare spaces.

If you would like further information, please contact us via telephone or email:

T: +44(0)1753 552 489

E: enquiries@owa-ceilings.co.uk


www.owa-ceilings.co.uk


OWA

S45 T15 lay-in system

Features:

- Premium quality, German engineered
- Removable lay-in tile enables access to services above
- Plain L0 is suitable for hygiene environments
- Perforated tiles provide excellent sound absorption
- Attractive tegular edge available (8 mm drop)

Collection	OWAtecta
Material	Galvanised sheet steel, approx. 0.5 mm
Modules*	600 x 600 mm (stocked)
Surface*	Perforated Rd1522 (black acoustic fleece)
Colour*	RAL 9010 pure white
Edges	Teg15 (edge 16)
	
Sound absorption	Rd1522 with acoustic pad: $\alpha_w = 0.90$ (class A) Rd1522 with fleece: $\alpha_w = 0.70$ (class C)
Sound insulation	Rd1522 with pad and mineral tile: $D_{nfw} = \text{up to } 45 \text{ dB}$ Rd1522 with fleece: $D_{nfw} = 16 \text{ dB}$
Reaction to fire	A2-s1,d0 (BS EN 13501-1)
Fire resistance	N/A
Cleanrooms	Yes (Plain L0 - ISO 14644-1 class 2)
Hygiene	Yes (Plain L0)
System Weight	Approx. 5.6 kg/m ²
Cleaning	Vacuum, wipe or dust only
Sustainability	100% recyclable
Warranty	Tile = 10 years, installed system = 30 years**



* Other sizes, colours and surfaces also available.

** The limited warranty is project specific. To comply, an accompanying warranty document must be completed and signed by the installing contractor and OWA project manager. If not, the standard 10 year product warranty will apply.